

AS  
cont  
B  
647

3. (Amended) A closure casing according to claim 2 wherein the resilient element comprises a laminar resilient strip overlying a surface portion of the casing.

4. (Amended) A closure casing according to claim 3 wherein said closure members comprise co-operating half shells having respective flanges around perimetral rims thereof, which rims are brought together when the casing is closed, and wherein said resilient element comprises a strip and/or stringer lying along the length of at least one of the flanges.

5. (Amended) A closure casing according to claim 4, wherein the flanges have a cavity therein adjacent the openings in the closure members across which said resilient strip spans.

6. (Amended) A closure casing according to Claim 1, wherein the first part of the toggle clamp mechanism has a transverse projection configured to engage the face of the closure member remote from the second part of the toggle clamp mechanism.

7. (Amended) A closure casing according to Claim 6 wherein there are a plurality of openings in the flanges of the closure members and a plurality of toggle clamp mechanisms spaced around at least part of a periphery of the closure members.

8. (Amended) A closure casing according to claim 6, wherein said transverse projection comprises a hooked end of the first part configured to engage said face of the closure member remote from the second part of the clamp mechanism.

9. (Amended) A closure casing according to Claim 1 wherein said second part of the toggle clamp mechanism comprises a body portion having two parallel flanges with respective aligned openings or cavities for receiving respective pivot pins

09980694-102401

of the first part such that the first part is located between the two parallel flanges, and an operating tab and/or lever that lies substantially parallel to a surface of one of the co-operating closure members when the toggle clamp mechanism is in the clamped position.

10. (Amended) A closure casing according to claim 9, wherein said body portion of the second part of the toggle clamp mechanism has a face extending generally transversely of the operating tab and/or lever and serving as a release member against which is applied a force to release the toggle clamp mechanism from the clamped position.

11. (Amended) A closure casing according to Claim 1 wherein there are a plurality of toggle clamps spaced along at least part of a perimeter of the casing and further comprising a sealing member located inwardly of the toggle clamps that seal the interior volume of the casing in the clamped position.

12. (Amended) A closure casing according to Claim 1, further comprising means to resist release of the toggle clamp mechanism.

13. (Amended) A closure casing according to claim 12, wherein the means to resist release of the toggle clamp mechanism acts to resist movement of the second part of the toggle clamp mechanism from its clamped to its release position.

14. (Amended) A closure casing according to claim 12 wherein the means to resist release of the toggle clamp mechanism resists withdrawal of the first part through the openings in the closure members.

15. (Amended) A closure casing according to Claim 14, wherein the means to resist release of the toggle clamp mechanism comprises at least one aperture in a

09980694-102401

08  
08.1  
B,  
08.1

member of the toggle clamp mechanism engageable by cooperating removable obstruction means for obstructing removal of the toggle clamp mechanism from the openings.

16. (Amended) A closure casing according Claim 15, wherein said at least one resilient element is relatively displaceable with respect to an adjacent one of the closure members so as to reduce the effective dimensions of the openings through which the first part of the toggle clamp mechanism passes whereby to obstruct withdrawal thereof.

17. (Amended) A closure casing according to claim 16 wherein said resilient element is retained in a channel which allows longitudinal movement of the resilient element.

18. (Amended) A closure casing according to claim 17, wherein said channel includes at least a part which is not rectilinear so as to apply stress to the resilient element when the channel and resilient element are in a juxtaposed position.

19. (Amended) A closure casing according to Claim 1, wherein the toggle clamp mechanism has means for engagement by a tool whereby to assist in turning the second part of the toggle clamp mechanism.

20. (Amended) A closure casing according to claim 19, wherein said means for engagement by a tool comprises at least one cavity in the second part of the toggle clamp mechanism.

09980694-102101

add  
B<sub>1</sub>  
cont

add  
B2.5